§ 98.338

each Waelz kiln or electrothermic furnace, as applicable to your facility, including documentation of any materials excluded from Equation GG-1 of this subpart that contribute less than 1 percent of the total carbon inputs to the process. You also must document the procedures used to ensure the accuracy of the measurements of materials fed, charged, or placed in an affected unit including, but not limited to, calibration of weighing equipment and other measurement devices. The estimated accuracy of measurements made with these devices must also be recorded, and the technical basis for these estimates must be provided.

§ 98.338 Definitions.

All terms used in this subpart have the same meaning given in the Clean Air Act and subpart A of this part.

Subpart HH—Municipal Solid Waste Landfills

§98.340 Definition of the source category.

- (a) This source category applies to municipal solid waste (MSW) landfills that accepted waste on or after January 1, 1980.
- (b) This source category does not include hazardous waste landfills, construction and demolition landfills, or industrial landfills.

(c) This source category consists of the following sources at municipal solid waste (MSW) landfills: Landfills, landfill gas collection systems, and landfill gas destruction devices (including flares).

§98.341 Reporting threshold.

You must report GHG emissions under this subpart if your facility contains a MSW landfill and the facility meets the requirements of §98.2(a)(1).

§98.342 GHGs to report.

- (a) You must report CH_4 generation and CH_4 emissions from landfills.
- (b) You must report CH_4 destruction resulting from landfill gas collection and combustion systems.
- (c) You must report under subpart C of this part (General Stationary Fuel Combustion Sources) the emissions of CO_2 , CH_4 , and N_2O from each stationary combustion unit following the requirements of subpart C.

§ 98.343 Calculating GHG emissions.

- (a) For all landfills subject to the reporting requirements of this subpart, calculate annual modeled CH₄ generation according to the applicable requirements in paragraphs (a)(1) through (a)(3) of this section.
- (1) Calculate annual modeled CH_4 generation using Equation HH-1 of this section.

$$G_{CH4} = \left[\sum_{x=S}^{T-1} \left\{ W_x L_{0,x} \left(e^{-k(T-x-1)} - e^{-k(T-x)} \right) \right\} \right]$$
 (Eq. HH-1)

Where:

 G_{CH4} = Modeled methane generation rate in reporting year T (metric tons CH_4).

X = Year in which waste was disposed.

- S = Start year of calculation. Use the year 50 years prior to the year of the emissions estimate, or the opening year of the landfill, whichever is more recent.
- T = Reporting year for which emissions are calculated.
- W_X = Quantity of waste disposed in the landfill in year X from tipping fee receipts or other company records (metric tons, as received (wet weight)).
- $\begin{array}{l} L_0 = CH_4 \ generation \ potential \ (metric \ tons \\ CH_4/metric \ ton \ waste) = MCF \times DOC \times DOC_F \\ \times \ F \times 16/12. \end{array}$
- MCF = Methane correction factor (fraction); default is 1.
- DOC = Degradable organic carbon from Table HH-1 of this subpart or measurement data, if available [fraction (metric tons C/metric ton wastel].
- DOC_F = Fraction of DOC dissimilated (fraction): default is 0.5.
- F = Fraction by volume of CH₄ in landfill gas from measurement data, if available (fraction); default is 0.5.